

Belastingtabellen  
persroosters voor heftrucks**Puntbelasting in kg. in een vlak van 100x100 mm voor vorkheftruckbelasting.**

Overspanning	Draagstaaf															Overspanning	
	25x5	30x3	30x5	40x3	40x4	40x5	50x3	50x5	60x5	70x5	80x5	90x5	100x5	120x5	140x5		150x5
200	1333	1152	1920	2048	2731	3413	3200	5333	7680	10453	13653						200
300	800	691	1152	1229	1638	2048	1920	3200	4608	6272	8192	10368	12800				300
400	571	494	823	878	1170	1463	1371	2286	3291	4480	7406	9143	13166				400
500	444	384	640	683	910	1138	1067	1778	2560	3483	4551	5760	7111	10240	13938		500
600	364	314	524	559	745	931	873	1455	2095	2851	3724	4713	5818	8378	11404	13091	600
700	308	266	443	473	630	788	738	1231	1772	2412	3151	3988	4923	7089	9649	11077	700
800	263	230	384	410	546	683	640	1067	1536	2091	2733	3456	4267	6144	8363	9600	800
900	206	203	339	361	482	602	565	941	1355	1845	2409	3049	3765	5421	7379	8471	900
1000	166	172	286	323	431	539	505	842	1213	1651	2156	2728	3368	4851	6602	7579	1000
1100	136	141	236	293	390	488	457	762	1097	1493	1950	2469	3048	4389	5973	6857	1100
1200	114	118	197	267	356	445	417	696	1002	1363	1781	2254	2783	4007	5454	6261	1200
1300	97	100	167	238	318	397	384	640	922	1254	1638	2074	2560	3686	5018	5760	1300
1400	83	86	144	205	273	341	356	593	853	1161	1517	1920	2370	3413	4646	5333	1400
1500	72	75	125	178	237	297	331	552	794	1081	1412	1788	2207	3178	4326	4966	1500
1600	64	66	110	156	208	260	305	508	743	1012	1321	1672	2065	2973	4046	4645	1600
1700	56	58	97	138	184	230	270	449	698	950	1241	1571	1939	2793	3801	4364	1700
1800	50	52	86	123	164	205	240	400	658	896	1170	1481	1829	2633	3584	4114	1800
1900			77	110	147	184	215	358	619	848	1107	1401	1730	2491	3390	3892	1900
2000			70	99	132	165	194	323	558	804	1050	1329	1641	2363	3216	3692	2000
2100			63	90	120	150	176	293	506	765	999	1264	1561	2248	3060	3512	2100
2200			58	82	109	136	160	266	460	729	953	1206	1488	2143	2917	3349	2200
2300			53	75	100	125	146	243	421	668	910	1152	1422	2048	2788	3200	2300
2400				69	92	114	134	223	386	613	871	1103	1362	1961	2669	3064	2400
2500				63	84	105	123	206	355	564	836	1058	1306	1881	2560	2939	2500

Draagstaafafstand 33,33 mm h.o.h.

Boven de streep max. spanning  
1600 kg/cm<sup>2</sup>.

Onder de streep max. doorbuiging  
1/200 x de overspanning.

**Veiligheidsfactor:**

tot de rekgrens 1.5,  
tot de breekgrens 2.1.

**Stootfactor:**

bij wisselende belasting  
de wioldruk met 1.3 vermenigvuldigen.